

## Ontero IC

Article number: 21470022

### LIGHT TECHNOLOGY

|                      |           |
|----------------------|-----------|
| LED                  | COB       |
| Light colour         | Sun       |
| Luminous flux        | 1070 lm   |
| System power         | 15 W      |
| Luminaire Efficiency | 71 lm/W   |
| Reflector            | OvalBasic |
| Beam angle           | 60° x 40° |

### LUMINAIRE

|                           |              |
|---------------------------|--------------|
| Rotation angle            | 330°         |
| Swivel angle              | +/- 90°      |
| Weight                    | 1.1 kg       |
| Protection rating . class | IP 20 . II   |
| Luminaire colour          | stratosilver |

### OPTIONEEL

RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, changeable reflector, honeycomb louver, Casambi model on inquiry



Surface-mounted luminaire with LED, rated life of the LED L80/B10 > 50000 h, chromaticity tolerance 3 SDCM (initial), LED hybrid technology, 3D silicone lens to reduce the proportion of scattered light, reflector with oval light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, segmented, exchangeable reflector unit in high-sheen black plastic, with glass cover, luminaire head die-cast aluminium, powder-coated, rotation angle 330°, swivel angle +/-90°, luminaire head/retention arm die-cast aluminium, stratosilver

In-Track-Adapter, Fix Current, black,  
max. 50 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.

