

# Ontero IC

Article number: 21480055

## LIGHT TECHNOLOGY

|                      |          |
|----------------------|----------|
| LED                  | COB      |
| Light colour         | Sun      |
| Luminous flux        | 1550 lm  |
| System power         | 23 W     |
| Luminaire Efficiency | 67 lm/W  |
| Reflector            | WallBeam |

## LUMINAIRE

|                           |              |
|---------------------------|--------------|
| Rotation angle            | 330°         |
| Swivel angle              | +/- 90°      |
| Weight                    | 1.1 kg       |
| Protection rating . class | IP 20 . II   |
| Luminaire colour          | stratosilver |

## OPTIONAL

RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, changeable reflector, Casambi model on inquiry



Surface-mounted luminaire with LED, rated life of the LED L80/B10 > 50000 h, chromaticity tolerance 3 SDCM (initial), reflector with asymmetrical light distribution pattern, primary reflector and kick reflector 99% pure aluminium in MIRO-Silver®, attachment with kick reflector to the ceiling approach of the light cone, exchangeable reflector unit in high-sheen black plastic, with glass cover, luminaire head die-cast aluminium, powder-coated, rotation angle 330°, swivel angle +/-90°, luminaire head/retention arm die-cast aluminium, stratosilver

In-Track-Adapter, Fix Current, black,  
max. 50 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.

