

Ontero IC

Article number: 21480120

LIGHT TECHNOLOGY


LED COB Light colour SpecialMeat Luminous flux 2110 lm 41 W System power Luminaire Efficiency 51 lm/W Reflector WallBeam

LUMINAIRE

Rotation angle 330° +90°/-90° Swivel angle 1.1 kg Weight Protection rating . class IP 20 . II Luminaire colour stratosilver

OPCJA

RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, changeable reflector, Casambi model on inquiry





Surface-mounted luminaire with LED, rated life of the LED L80/B10 > 50000 h, chromaticity tolerance 2 SDCM (initial), reflector with asymmetrical light distribution pattern, primary reflector and kick reflector 99% pure aluminium in MIRO-Silver®, attachment with kick reflector to the ceiling approach of the light cone, exchangeable reflector unit in high-sheen black plastic, with glass cover, luminaire head die-cast aluminium, powder-coated, rotation angle 330°, swivel angle +90°/-90°, luminaire head/retention arm die-cast aluminium, stratosilver

Multiadapter black, inclusive driver unit: 220-240 V~ / 50-60 Hz, max. 64 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.













18.10.2025 www.baero.com