

# Ontero ID

Article number: 20630042

## LIGHT TECHNOLOGY

|                      |         |
|----------------------|---------|
| LED                  | COB     |
| Light colour         | BeCool  |
| Luminous flux        | 2020 lm |
| System power         | 23 W    |
| Luminaire Efficiency | 88 lm/W |
| Reflector            | Medium  |
| Beam angle           | 25°     |

## LUMINAIRE

|                           |             |
|---------------------------|-------------|
| Rotation angle            | 330°        |
| Swivel angle              | 90°         |
| Weight                    | 1.3 kg      |
| Protection rating . class | IP 20 . I   |
| Luminaire colour          | stratoblack |

## OPCJA


RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver



Surface-mounted luminaire with LED, rated life of the LED L80/B10 > 50000 h, colour rendering index CRI > 96, chromaticity tolerance 3 SDCM (initial), LED hybrid technology, 3D silicone lens to reduce the proportion of scattered light, reflector with circular light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, segmented and faceted, exchangeable reflector unit in high-sheen black plastic, with glass cover, rotation angle 330°, swivel angle 90°, luminaire housing die-cast aluminium, powder-coated, stratoblack

Multiadapter black, inclusive driver unit: 220-240 V~ / 50-60 Hz, max. 34 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



|       |      |            |
|-------|------|------------|
| 1.0 m | 0.44 | 7992.0     |
| 2.0 m | 0.88 | 1998.0     |
| 3.0 m | 1.32 | 888.0      |
| 4.0 m | 1.76 | 500.0      |
| 5.0 m | 2.20 | 320.0      |
| Ø (m) |      | E0(0°)(lx) |

