

Ontero RA 90


Article number: 20390007

LIGHT TECHNOLOGY

LED	COB
Light colour	830
Luminous flux	2950 lm
System power	23 W
Luminaire Efficiency	127 lm/W
Reflector	Medium
Beam angle	24°

LUMINAIRE


Rotation angle	350°
Swivel angle	135°
Weight	0.9 kg
Protection rating . class	IP 20 . I
Luminaire colour	stratoblack



Surface-mounted luminaire with LED, luminaire housing and head die cast aluminium, powder-coated, rated life of the LED L80/B10 > 50000 h, colour rendering index CRI > 80, chromaticity tolerance 2 SDCM (initial), reflector with circular light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, powder-coated, rotation angle 350°, swivel angle 135°, luminaire housing/head die-cast aluminium,, stratoblack

Multiadapter black, inclusive driver unit: 220-240 V~ / 50-60 Hz, max. 34 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



1.0 m	0.45	10191.0
2.0 m	0.90	2548.0
3.0 m	1.35	1133.0
4.0 m	1.80	637.0
5.0 m	2.25	408.0
	Ø (m)	E0(0°)(lx)

