

## Ontero RA 90

Article number: 20390010

### LIGHT TECHNOLOGY

|                      |          |
|----------------------|----------|
| LED                  | COB      |
| Light colour         | 830      |
| Luminous flux        | 2950 lm  |
| System power         | 23 W     |
| Luminaire Efficiency | 127 lm/W |
| Reflector            | Medium   |
| Beam angle           | 24°      |

### LUMINAIRE

|                           |             |
|---------------------------|-------------|
| Rotation angle            | 350°        |
| Swivel angle              | 135°        |
| Weight                    | 0.9 kg      |
| Protection rating . class | IP 20 . I   |
| Luminaire colour          | stratowhite |



Surface-mounted luminaire with LED, luminaire housing and head die cast aluminium, powder-coated, rated life of the LED L80/B10 > 50000 h, colour rendering index CRI > 80, chromaticity tolerance 2 SDCM (initial), reflector with circular light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, powder-coated, rotation angle 350°, swivel angle 135°, luminaire housing/head die-cast aluminium,, stratowhite

Multiadapter black, inclusive driver unit: 220-240 V~ / 50-60 Hz, max. 34 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.

