

Ontero XR

Article number: 20530040

LIGHT TECHNOLOGY


LED COB
Light colour BeColor
Luminous flux 2740 lm
System power 34 W
Luminaire Efficiency 81 lm/W
Reflector Spot
Beam angle 20°

LUMINAIRE

Rotation angle 330°
Swivel angle +85°/-85°
Weight 0.54 kg
Protection rating . class IP 20 . II
Luminaire colour stratowhite

OPCJA

RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry (only luminaire head and holding arm), surface alloys on inquiry, Casambi on inquiry, honeycomb louver, blends







Surface-mounted luminaire with LED, rated life of the LED L80/B10 > 50000 h, colour rendering index CRI > 96, chromaticity tolerance 2 SDCM (initial), reflector with circular light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, rotation angle 330°, swivel angle +85°/-85°, luminaire head/retention arm die-cast aluminium, powder-coated, stratowhite

In-Track-Adapter, white, inclusive driver unit, Fix Current, 220-240 V~ / 50-60 Hz, max. 25 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.













www.baero.com 17.10.2025