

## Ontero XR

Article number: 20780014

### LIGHT TECHNOLOGY

|                      |          |
|----------------------|----------|
| LED                  | COB      |
| Light colour         | 835      |
| Luminous flux        | 2030 lm  |
| System power         | 15 W     |
| Luminaire Efficiency | 135 lm/W |
| Reflector            | Medium   |
| Beam angle           | 25°      |

### LUMINAIRE

|                           |              |
|---------------------------|--------------|
| Rotation angle            | 400°         |
| Swivel angle              | +85° / -85°  |
| Weight                    | 0.8 kg       |
| Protection rating . class | IP 20 . I    |
| Luminaire colour          | stratosilver |

### OPTIONAL

RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry (only luminaire head and holding arm) surface alloys on inquiry, honeycomb louver, blends



Surface-mounted luminaire with LED, rated life of the LED L80/B10 > 50000 h, colour rendering index CRI > 80, chromaticity tolerance 2 SDCM (initial), reflector with circular light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, segmented and faceted, 3D lens silicon to reduce the proportion of scattered light, rotation angle 400°, swivel angle +85°/-85°, luminaire head/retention arm die-cast aluminium, powder-coated, stratosilver, power-adaptor, black, inclusive fix current driver unit: 220-240 V~ / 50-60 Hz, max. 34 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



|       |       |             |
|-------|-------|-------------|
| 1.0 m | 0.44  | 8031.1      |
| 2.0 m | 0.88  | 2007.8      |
| 3.0 m | 1.32  | 892.3       |
| 4.0 m | 1.76  | 501.9       |
| 5.0 m | 2.20  | 321.2       |
|       | Ø (m) | E0(0°) [lx] |

