

Ontero XR

Article number: 20820011

LIGHT TECHNOLOGY


LED COB
Light colour BeColor
Luminous flux 990 lm
System power 15 W
Luminaire Efficiency 66 lm/W
Reflector NarrowSpot
Beam angle 10°

LUMINAIRE

Rotation angle 400°
Swivel angle +85° / -85°
Weight 0.8 kg
Protection rating . class IP 20 . I
Luminaire colour stratosilver

OPCJA


RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry (only luminaire head and holding arm) surface alloys on inquiry, honeycomb louver, blends






Surface-mounted luminaire with LED, rated life of the LED L80/B10 > 50000 h, colour rendering index CRI > 95, chromaticity tolerance 2 SDCM (initial), rotation-symmetrical reflector with circular light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, segmented and faceted, 3D lens silicon to reduce the proportion of scattered light, rotation angle 400°, swivel angle +85°/-85°, luminaire head/retention arm die-cast aluminium, powder-coated, stratosilver, power-adapter, black, inclusive DALI driver unit: 220-240 V~ / 50-60 Hz, max. 95 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.















www.baero.com 20.10.2025