

# Ontero XR

Article number: 20840089

## LIGHT TECHNOLOGY



|                      |          |
|----------------------|----------|
| LED                  | COB      |
| Light colour         | 840      |
| Luminous flux        | 3780 lm  |
| System power         | 34 W     |
| Luminaire Efficiency | 111 lm/W |
| Reflector            | Medium   |
| Beam angle           | 24°      |

## LUMINAIRE

|                           |             |
|---------------------------|-------------|
| Rotation angle            | 400°        |
| Swivel angle              | +85° / -85° |
| Weight                    | 0.69 kg     |
| Protection rating . class | IP 20 . I   |
| Luminaire colour          | stratoblack |


## OPCJA

RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry  
(only luminaire head and holding arm) surface alloys on inquiry,  
honeycomb louver, blends



Surface-mounted luminaire with LED, rated life of the LED L80/B10 > 50000 h, colour rendering index CRI > 80, chromaticity tolerance 2 SDCM (initial), reflector with circular light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, segmented and faceted, 3D lens silicon to reduce the proportion of scattered light, rotation angle 400°, swivel angle +85°/-85°, luminaire head/retention arm die-cast aluminium, powder-coated, stratoblack, power-adaptor, black, inclusive DALI driver unit: 220-240 V~ / 50-60 Hz, max. 95 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



|       |      |             |
|-------|------|-------------|
| 1.0 m | 0.44 | 14954.4     |
| 2.0 m | 0.88 | 3738.6      |
| 3.0 m | 1.32 | 1661.6      |
| 4.0 m | 1.76 | 934.7       |
| 5.0 m | 2.20 | 598.2       |
| Ø (m) |      | E0(0°) [lx] |

