

Ontero ID

Article number: 20940008

LIGHT TECHNOLOGY



| | |
|----------------------|----------|
| LED | SMD Line |
| Light colour | 927 |
| Luminous flux | 1810 lm |
| System power | 28 W |
| Luminaire Efficiency | 65 lm/W |
| Reflector | WallWash |

LUMINAIRE

| | |
|---------------------------|--------------|
| Rotation angle | 330° |
| Weight | 1.24 kg |
| Protection rating . class | IP20 . I |
| Luminaire colour | stratosilver |

OPCJA

RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver



Surface-mounted wallwasher with LED, rated life of the LED L80/B10 > 50000 h, colour rendering index CRI > 90, chromaticity tolerance 3 SDCM (initial), reflector with asymmetrical light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, end caps die-cast aluminium, powder-coated, rotation angle 330°, luminaire housing aluminium extrusion profile, stratosilver

Multiadapter black, inclusive driver unit: 220-240 V~ / 50-60 Hz, max. 37 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.

