

Intara RC 625

Article number: 50280004

LIGHT TECHNOLOGY

LED SMD Line
Light colour 927
Luminous flux 2200 lm
System power 33 W
Luminaire Efficiency 67 lm/W
Reflector WallWash
Beam angle 1 x 20°




Weight 0.9kg without driver

Protection rating . class IP 20 . III Luminaire colour black

OPCJA

Mounting Accessories DALI driver on request





recessed luminaire with LED, rated life of the LED L80/B10 > 50000 h, color rendering index CRI > 90, chromaticity point tolerance 3 SDCM (initial), Reflector with asymerical light distribution pattern, 99.99% pure aluminium reflector made of MIRO-SILVER®, aluminium luminaire housing and frame, anodized, separate driver unit.

If ceilings with thickness of more than 20mm are fitted the ceiling cutout will differ. Please pay attention to the dimension in the drawing.

76500032 driver unit, fix current

220-240 V / 50-60 Hz, 900 mA, with GST18/3-pin connector, incl. 3-conductor feed-through wiring, camera-compatible, up to $2.5~\rm KV$ interference resistance, SELV, max. 52 Stk. / B16 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.











