

## Intara RC 600

Article number: 50350001

## LIGHT TECHNOLOGY

LED SMD Line
Light colour 927
Luminous flux 2200 lm
System power 33 W
Luminaire Efficiency 67 lm/W
Reflector WallWash
Beam angle 1 x 20°


## **LUMINAIRE**

Weight 0.9kg without driver

Protection rating . class IP 20 . III Luminaire colour black

## **OPCJA**

Profile aperture DALI driver on request





Recessed lumionaire for grid ceiling with LED, rated life of the LED L80/B10 > 50000 h, color rendering index CRI > 90, chromaticity point tolerance 3 SDCM (initial), Reflector with asymerical light distribution pattern, 99.99% pure aluminium reflector made of MIRO-SILVER®, aluminium luminaire housing and frame, anodized, separate driver unit.

If ceiling systems with bevelled inlay panels are used additional profile must be used (product number: 5036 0000 00114). Please order these separately for each luminaire.

76500032 driver unit, fix current

220-240 V / 50-60 Hz, 900 mA, with GST18/3-pin connector, incl. 3-conductor feed-through wiring, camera-compatible, up to 2.5 KV interference resistance, SELV, max. 52 Stk. / B16 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.











