

Ontero TX

Article number: 21370003

LIGHT TECHNOLOGY

LED SMD-Board Light colour 840

Luminous flux

System power

38 W - 72 W

Luminaire Efficiency

Reflector

6140 - 10860 lm

38 W - 72 W


162 lm/W - 151 lm/W

doppelt asymmetrisch

Beam angle $2 \times 20^{\circ}$

LUMINAIRE

Rotation angle 330°
Weight 3.1 kg
Protection rating . class IP 20 . I
Luminaire colour matt black





Surface-mounted luminaire with LED, rated life of the LED L80/B50 > 50000 h, colour rendering index CRI > 80, chromaticity tolerance 3 SDCM (initial), double asymmetrical light distribution pattern, lens made of PMMA, Driver with power selection via DIP switch, 8 possible levels: 38 W (5900 lm), 42 W (6540 lm), 47 W (7150 lm), 52 W (7770 lm), 57 W (7850 lm), 62W (8950 lm), 67 W (9550 lm), 72 W (10130 lm), 62 W preselected, rotation angle 330°, luminaire housing sheet steel, powder-coated, matt black,

Multiadapter black, inclusive driver unit: 220-240 V~/50-60 Hz, max. 24 luminaires per circuit (B16A fuse), DIP-Switch 38W-72W (default 53W), temperature protection

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.

