

## beledi XS

Article number: 70620802

### LIGHT TECHNOLOGY

|                      |            |
|----------------------|------------|
| LED                  | SMD linear |
| Light colour         | 840        |
| Luminous flux        | 4000 lm    |
| System power         | 25.5 W     |
| Luminaire Efficiency | 157 lm/W   |
| Reflector            | NarrowBeam |

### LUMINAIRE

|                           |           |
|---------------------------|-----------|
| Weight                    | 3.2 kg    |
| Protection rating . class | IP 40 . I |
| Luminaire colour          | black     |

### OPTIONAL


Mounting Accessories



Light band with LED, rated life of the LED L80/B50 > 50000 h, colour rendering index CRI > 80, reflector with homogeneous light distribution pattern, lens optics made of PMMA, luminaire insert sheet steel, powder-coated, black

driver unit: 220-240 V~ / 50-60 Hz, max. 24 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



|       |           |            |
|-------|-----------|------------|
| 1.0 m | 1.43 0.62 | 4653.0     |
| 2.0 m | 2.86 1.24 | 1163.0     |
| 3.0 m | 4.29 1.86 | 517.0      |
| 4.0 m | 5.72 2.48 | 291.0      |
| 5.0 m | 7.15 3.10 | 186.0      |
| Ø (m) |           | E0(0°)(lx) |

