

beledi XS

Article number: 70660805

LIGHT TECHNOLOGY

| | |
|----------------------|---------------|
| LED | SMD linear |
| Light colour | 840 |
| Luminous flux | 6000 lm |
| System power | 42 W |
| Luminaire Efficiency | 143 lm/W |
| Reflector | Xtra WideBeam |

LUMINAIRE

| | |
|---------------------------|-----------|
| Weight | 3.2 kg |
| Protection rating . class | IP 40 . I |
| Luminaire colour | black |

OPTIONAL

Mounting Accessories



Light band with LED, rated life of the LED L80/B50 > 50000 h, colour rendering index CRI > 80, reflector with homogeneous light distribution pattern, lens optics made of PMMA, luminaire insert sheet steel, powder-coated, black

driver unit: 220-240 V~ / 50-60 Hz, max. 24 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



| | | |
|-------|-------------|------------|
| 1.0 m | 2.94 2.48 | 1942.0 |
| 2.0 m | 5.88 4.96 | 485.0 |
| 3.0 m | 8.82 7.44 | 216.0 |
| 4.0 m | 11.76 9.92 | 121.0 |
| 5.0 m | 14.70 12.40 | 78.0 |
| Ø (m) | | E0(0°)(lx) |

