

# beledi XS

Article number: 70680521

## LIGHT TECHNOLOGY


|                      |            |
|----------------------|------------|
| LED                  | SMD linear |
| Light colour         | 840        |
| Luminous flux        | 6000 lm    |
| System power         | 43 W       |
| Luminaire Efficiency | 140 lm/W   |
| Reflector            | SoftBeam+  |

## LUMINAIRE

|                           |           |
|---------------------------|-----------|
| Weight                    | 3.2 kg    |
| Protection rating . class | IP 40 . I |
| Luminaire colour          | silver    |

## OPTIONAL


Mounting Accessories



Light band with LED, rated life of the LED L80/B50 > 50000 h, colour rendering index CRI > 80, reflector with homogeneous light distribution pattern, lens optics made of PMMA, luminaire insert sheet steel, powder-coated, silver

driver unit: 220-240 V~ / 50-60 Hz, max. 24 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



|       |             |        |
|-------|-------------|--------|
| 1.0 m | 3.13 2.60   | 1932.0 |
| 2.0 m | 6.26 5.20   | 483.0  |
| 3.0 m | 9.39 7.80   | 215.0  |
| 4.0 m | 12.52 10.40 | 121.0  |
| 5.0 m | 15.65 13.00 | 77.0   |
| Ø (m) | E0(0°)(lx)  |        |

