

## beledi XS

Article number: 70680719

### LIGHT TECHNOLOGY

LED	SMD linear
Light colour	830
Luminous flux	4800 lm
System power	35 W
Luminaire Efficiency	137 lm/W
Reflector	SoftBeam+

### LUMINAIRE

Weight	3.2 kg
Protection rating . class	IP 40 . I
Luminaire colour	black

### OPTIONAL


Mounting Accessories



Light band with LED, rated life of the LED L80/B50 > 50000 h, colour rendering index CRI > 80, reflector with homogeneous light distribution pattern, lens optics made of PMMA, luminaire insert sheet steel, powder-coated, black

driver unit: 220-240 V~ / 50-60 Hz, max. 24 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



Distance (m)	Beam Diameter (m)	Beam Area (m²)	Beam Diameter (m)	Beam Area (m²)
1.0 m	0.90	0.64	3.13	2.60
2.0 m	1.80	3.24	6.26	5.20
3.0 m	2.70	7.29	9.39	7.80
4.0 m	3.60	12.96	12.52	10.40
5.0 m	4.50	20.25	15.65	13.00

Ø (m) E0(0°)(lx)

