

## Intara TX

Article number: 50800002

## LIGHT TECHNOLOGY

LED SMD-Board
Light colour 835
Luminous flux 6480 lm
System power 45 W
Luminaire Efficiency 144 lm/W

Reflector doppelt asymmetrisch


Beam angle  $2 \times 20^{\circ}$ 

## **LUMINAIRE**

Weight 3.2 kg
Protection rating . class IP 20 . I
Luminaire colour matt black

## **OPTIONAL**

Accessories for feed-through wiring, cover stripes






Lay in luminaire with LED, rated life of the LED L80/B50 > 50000 h, colour rendering index CRI > 80, chromaticity tolerance 3 SDCM (initial), double asymmetrical light distribution pattern, lens made of PMMA, luminaire housing sheet steel, powder-coated, matt black

Driver with adjustable system power in 8 steps (38 W to 64 W), choice by DIP-Switch, 220-240 V~/50-60 Hz, max. 16 Pcs. luminaires per circut (B16A fuse).

Order ceiling attachment with visible supporting profile separately: 5080Z600 B-Set for Ceiling Systems 600 5080Z625 B-Set for Ceiling Systems 625

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.











www.baero.com 17.10.2025