BÄRO
Retail
Lighting

# Intara TX

Article number: 50810002

## LIGHT TECHNOLOGY

| | |
|---|---|
| LED | SMD-Board |
| Light colour | 835 |
| Luminous flux | 8780 lm |
| System power | 64 W |
| Luminaire Efficiency | 137 lm/W |
| Reflector | WideFlood |
| Beam angle | 60° |

## LUMINAIRE

| | |
|---|---|
| Weight | 3.2 kg |
| Protection rating . class | IP 20 . I |
| Luminaire colour | matt black |

## OPTIONAL

Accessories for feed-through wiring,
cover stripes



Lay in luminaire with LED, rated life of the LED L80/B50 > 50000 h, colour rendering index CRI > 80, chromaticity tolerance 3 SDCM (initial), wide, homogeneous light distribution pattern, TIR-lens made of PMMA, luminaire housing sheet steel, powder-coated, matt black

Driver with adjustable system power in 8 steps (38 W to 64 W), choice by DIP-Switch, 220-240 V~ / 50-60 Hz, max. 16 Pcs. luminaires per circut (B16A fuse).

Order ceiling attachment with visible supporting profile separately:
5080Z600 B-Set for Ceiling Systems 600
5080Z625 B-Set for Ceiling Systems 625

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.