

## Intara TX

Article number: 50850002

### LIGHT TECHNOLOGY

|                      |                |
|----------------------|----------------|
| LED                  | SMD-Board      |
| Light colour         | 835            |
| Luminous flux        | 8310 lm        |
| System power         | 60 W           |
| Luminaire Efficiency | 137 lm/W       |
| Reflector            | Xtra WideFlood |
| Beam angle           | 90°            |

### LUMINAIRE

|                           |            |
|---------------------------|------------|
| Weight                    | 3.2 kg     |
| Protection rating . class | IP 20 . I  |
| Luminaire colour          | matt black |

### OPTIONEEL

Accessories for feed-through wiring,  
cover stripes



Lay in luminaire with LED, rated life of the LED L80/B50 > 50000 h, colour rendering index CRI > 80, chromaticity tolerance 3 SDCM (initial), extra wide, homogeneous light distribution pattern, TIR-lens made of PMMA, luminaire housing sheet steel, powder-coated, matt black

Driver with adjustable system power in 8 steps (38 W to 64 W), choice by DIP-Switch, 220-240 V~ / 50-60 Hz, max. 16 Pcs. luminaires per circuit (B16A fuse).

Order ceiling attachment with visible supporting profile separately:  
5080Z600 B-Set for Ceiling Systems 600  
5080Z625 B-Set for Ceiling Systems 625

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



|       |               |                  |
|-------|---------------|------------------|
| 1     | 2.63 . 2.50   | 382.5            |
| 2     | 5.26 . 5.00   | 96.6             |
| 3     | 7.89 . 7.50   | 42.5             |
| 4     | 10.52 . 10.00 | 23.9             |
| 5     | 13.15 . 12.50 | 15.3             |
| h (m) | Ø (m)         | E0 (0°) (lx/klm) |

