

## Intara TX

Article number: 50850004

### LIGHT TECHNOLOGY

|                      |                |
|----------------------|----------------|
| LED                  | SMD-Board      |
| Light colour         | 830            |
| Luminous flux        | 7000 lm        |
| System power         | 53 W           |
| Luminaire Efficiency | 132 lm/W       |
| Reflector            | Xtra WideFlood |
| Beam angle           | 90°            |

### LUMINAIRE

|                           |            |
|---------------------------|------------|
| Weight                    | 3.2 kg     |
| Protection rating . class | IP 20 . I  |
| Luminaire colour          | matt white |

### OPTIONEEL

Accessories for feed-through wiring,  
cover stripes




Lay in luminaire with LED, rated life of the LED L80/B50 > 50000 h, colour rendering index CRI > 80, chromaticity tolerance 3 SDCM (initial), extra wide, homogeneous light distribution pattern, TIR-lens made of PMMA, luminaire housing sheet steel, powder-coated, matt white

Driver with adjustable system power in 8 steps (38 W to 64 W), choice by DIP-Switch, 220-240 V~ / 50-60 Hz, max. 16 Pcs. luminaires per circuit (B16A fuse).

Order ceiling attachment with visible supporting profile separately:  
5080Z600 B-Set for Ceiling Systems 600  
5080Z625 B-Set for Ceiling Systems 625

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



|       |               |                  |
|-------|---------------|------------------|
| 1     | 2,63 . 2,50   | 382,5            |
| 2     | 5,26 . 5,00   | 96,6             |
| 3     | 7,89 . 7,50   | 42,5             |
| 4     | 10,52 . 10,00 | 23,9             |
| 5     | 13,15 . 12,50 | 15,3             |
| h (m) | Ø (m)         | E0 (0°) (lx/klm) |

