

Pendiro TX

Article number: 80840003

LIGHT TECHNOLOGY

| | |
|----------------------|----------------------|
| LED | SMD-Bord |
| Light colour | 840 |
| Luminous flux | 7650 lm |
| System power | 53 W |
| Luminaire Efficiency | 144 lm/W |
| Reflector | doppelt asymmetrisch |
| Beam angle | 2 x 20° |

LUMINAIRE

| | |
|---------------------------|---------------|
| Rotation angle | +165° / -165° |
| Weight | 3.7 kg |
| Protection rating . class | IP 20 . I |
| Luminaire colour | matt black |



Suspended luminaire with LED, rated life of the LED L80/B50 > 50000 h, colour rendering index CRI > 80, chromaticity tolerance 3 SDCM (initial), double asymmetrical light distribution pattern, lens made of PMMA, luminaire housing sheet steel, powder-coated, matt black, power supply via suspension cables

Canopy with SELV driver with adjustable system power in 8 steps (38 W to 64 W), choice by DIP-Switch, 220-240 V~ / 50-60 Hz, max. 16 Pcs. luminaires per circuit (B16A fuse), Steel sheet powder-coated

Order separately:

- 76500079 E-Set with Canopy, black
- 76500081 E-Set with Canopy, white
- 76500083 E-Set with Canopy, DALI, black
- 76500085 E-Set with Canopy, DALI, white
- 76500078 E-Set for 3-Ph Track, black
- 76500080 E-Set for 3-Ph Track, white
- 76500082 E-Set for 3-Ph Track, DALI, black
- 76500084 E-Set for 3-Ph Track, DALI, white

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.

