

## Pendiro TX

Article number: 80840006

## LIGHT TECHNOLOGY


LED SMD-Bord
Light colour 840
Luminous flux 5580 lm
System power 38 W
Luminaire Efficiency 147 lm/W

Reflector doppelt asymmetrisch

Beam angle  $2 \times 20^{\circ}$ 

## **LUMINAIRE**

Rotation angle +165° / -165°
Weight 3.7 kg
Protection rating . class IP 20 . I
Luminaire colour matt white






Suspended luminaire with LED, rated life of the LED L80/B50 > 50000 h, colour rendering index CRI > 80, chromaticity tolerance 3 SDCM (initial), double asymmetrical light distribution pattern, lens made of PMMA, luminaire housing sheet steel, powder-coated, matt white, power supply via suspension cables

Canopy with SELV driver with adjustable system power in 8 steps (38 W to 64 W), choice by DIP-Switch, 220-240  $V\sim$  / 50-60 Hz, max. 16 Pcs. luminaires per circut (B16A fuse), Steel sheet powder-coated

## Order separately:

76500079 E-Set with Canopy, black 76500081 E-Set with Canopy, white 76500083 E-Set with Canopy, DALI, black 76500085 E-Set with Canopy, DALI, white 76500078 E-Set for 3-Ph Track, black 76500080 E-Set for 3-Ph Track, white 76500082 E-Set for 3-Ph Track, DALI, black 76500084 E-Set for 3-Ph Track, DALI, white

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.











www.baero.com 28.10.2025