

Pendiro TX

Article number: 80860001

LIGHT TECHNOLOGY

| | |
|----------------------|----------------|
| LED | SMD-Bord |
| Light colour | 830 |
| Luminous flux | 6560 lm |
| System power | 49 W |
| Luminaire Efficiency | 134 lm/W |
| Reflector | Xtra WideFlood |
| Beam angle | 90° |

LUMINAIRE

| | |
|---------------------------|---------------|
| Rotation angle | +165° / -165° |
| Weight | 3.7 kg |
| Protection rating . class | IP 20 . I |
| Luminaire colour | matt black |




Suspended luminaire with LED, rated life of the LED L80/B50 > 50000 h, colour rendering index CRI > 80, chromaticity tolerance 3 SDCM (initial), extra wide, homogeneous light distribution pattern, TIR-lens made of PMMA, luminaire housing sheet steel, powder-coated, matt black, power supply via suspension cables

Canopy with SELV driver with adjustable system power in 8 steps (38 W to 64 W), choice by DIP-Switch, 220-240 V~ / 50-60 Hz, max. 16 Pcs. luminaires per circuit (B16A fuse), Steel sheet powder-coated

Order separately:

- 76500079 E-Set with Canopy, black
- 76500081 E-Set with Canopy, white
- 76500083 E-Set with Canopy, DALI, black
- 76500085 E-Set with Canopy, DALI, white
- 76500078 E-Set for 3-Ph Track, black
- 76500080 E-Set for 3-Ph Track, white
- 76500082 E-Set for 3-Ph Track, DALI, black
- 76500084 E-Set for 3-Ph Track, DALI, white

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



| h (m) | Ø (m) | E0 (0°) (lx/klm) |
|-------|---------------|------------------|
| 1 | 2.63 . 2.50 | 382.5 |
| 2 | 5.26 . 5.00 | 96.6 |
| 3 | 7.89 . 7.50 | 42.5 |
| 4 | 10.52 . 10.00 | 23.9 |
| 5 | 13.15 . 12.50 | 15.3 |

