

## Intara CX

Article number: 51470012

## LIGHT TECHNOLOGY

LED СОВ Light colour Sun Luminous flux 2240 lm 41 W System power Luminaire Efficiency 55 lm/W Reflector OvalBasic Beam angle 60° x 40°

## **LUMINAIRE**

350° Rotation angle Swivel angle +30° / -30° Weight 0.70 kg Protection rating . class IP20.III Luminaire colour black

## **OPTIONAL**

RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver





Recessed directional spot, flush with ceiling with LED, rated life of the LED L80/B10 > 50000 h, chromaticity tolerance 3 SDCM (initial), reflector with oval light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, segmented, exchangeable reflector unit in high-sheen black plastic, with glass cover, luminaire head designed as heat sink die-cast aluminium, black anodized, rotation angle 350°, swivel angle +30°/-30°, Ceiling plaster die-cast aluminum, trim plastic injection molding, black, separate driver unit

driver unit, Fix Current,

220-240 V / 50-60 Hz, camera-compatible, up to 2.5 KV interference resistance, SELV, max. 22 luminaires per circuit (B16A fuse)

driver unit, DALI,

220-240 V / 50-60 Hz, with GST18/5-pin connector, incl. 5-conductor feedthrough wiring, camera-compatible, up to 2.5 KV interference resistance, SELV, max. 22 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.

















