

Intara CX

Article number: 51380011

LIGHT TECHNOLOGY


LED COB
Light colour SpecialMeat
Luminous flux 2030 lm
System power 41 W
Luminaire Efficiency 50 lm/W
Reflector Flood
Beam angle 40°

LUMINAIRE

Rotation angle 350°
Swivel angle +30°/-30°
Weight 0.72 kg
Protection rating . class IP20 . III
Luminaire colour black

OPCJA

RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver





Recessed directional spot with LED, rated life of the LED L80/B10 > 50000 h, chromaticity tolerance 2 SDCM (initial), reflector with circular light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, segmented and faceted, exchangeable reflector unit in high-sheen black plastic, with glass cover, luminaire head designed as heat sink die-cast aluminium, black anodized, rotation angle 350°, swivel angle +30°/-30°, assembly ring diecast aluminum, front ring and trim in plastic, plastic clamp spring for ceiling attachment, black, separate driver unit


76500037 driver unit, Fix Current,


220-240 V / 50-60 Hz, 1050 mA, camera-compatible, up to 2.5 KV interference resistance, SELV, max. 22 luminaires per circuit (B16A fuse)

76500042 driver unit, DALI,

220-240 V / 50-60 Hz, 1050 mA, with GST18/5-pin connector, incl. 5-conductor feed-through wiring, camera-compatible, up to $2.5~{\rm KV}$ interference resistance, SELV, max. 22 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



















www.baero.com 17.10.2025