

Intara CX

Article number: 51410022

LIGHT TECHNOLOGY


| | |
|----------------------|------------|
| LED | COB |
| Light colour | PearlWhite |
| Luminous flux | 1930 lm |
| System power | 23 W |
| Luminaire Efficiency | 83 lm/W |
| Reflector | Downlight |
| Beam angle | 60° |

LUMINAIRE

| | |
|---------------------------|------------|
| Weight | 0.67 kg |
| Protection rating . class | IP20 . III |
| Luminaire colour | white |

OPTIONAL

RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver




Recessed downlight with LED, rated life of the LED L80/B10 > 50000 h, colour rendering index CRI > 90, chromaticity tolerance 2 SDCM (initial), reflector with homogeneous light distribution pattern, diffuser lens, translucent, darklight reflector, aluminium, metallised, highgloss, luminaire head die-cast aluminium, powder-coated, mounting ring die-cast aluminum, front ring and coverblind plastic, white, separate driver unit

76500034 driver unit, Fix Current, 220-240 V / 50-60 Hz, 600 mA, camera-compatible, up to 2.5 KV interference resistance, SELV, max. 34 luminaires per circuit (B16A fuse)

76500039 driver unit, DALI, 220-240 V / 50-60 Hz, 600 mA, with GST18/5-pin connector, incl. 5-conductor feed-through wiring, camera-compatible, up to 2.5 KV interference resistance, SELV, max. 24 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



| | | |
|-------|-------|-------------|
| 1.0 m | 1.28 | 1819.1 |
| 2.0 m | 2.56 | 454.8 |
| 3.0 m | 3.84 | 202.1 |
| 4.0 m | 5.12 | 113.7 |
| 5.0 m | 6.40 | 72.8 |
| | Ø (m) | E0(0°) [lx] |

