

## Intara EC 125

Article number: 51190107

### LIGHT TECHNOLOGY


|                      |             |
|----------------------|-------------|
| LED                  | COB         |
| Light colour         | SpecialMeat |
| Luminous flux        | 1920 lm     |
| System power         | 34 W        |
| Luminaire Efficiency | 57 lm/W     |
| Reflector            | OvalBasic   |
| Beam angle           | 60° x 30°   |

### LUMINAIRE

|                           |              |
|---------------------------|--------------|
| Rotation angle            | 170°         |
| Swivel angle              | 65°          |
| Weight                    | 1.9 kg       |
| Protection rating . class | IP 20 . III  |
| Luminaire colour          | stratosilver |

### OPTIONAL

RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver




Semi-recessed luminaire with LED, rated life of the LED L80/B10 > 50000 h, chromaticity tolerance 2 SDCM (initial), reflector with oval light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, luminaire head die-cast aluminium, powder-coated, rotation angle 170°, swivel angle 65°, mounting frame sheet steel, lightproof, stratosilver, separate driver unit

76500076 driver unit, Fix Current, 220-240 V / 50-60 Hz, 850 mA, camera-compatible, up to 2.5 KV interference resistance, SELV, max. 34 luminaires per circuit (B16A fuse)

76500077 driver unit, DALI, 220-240 V / 50-60 Hz, 850 mA, with GST18/5-pin connector, incl. 5-conductor feed-through wiring, camera-compatible, up to 2.5 KV interference resistance, SELV, max. 24 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



|       |             |             |
|-------|-------------|-------------|
| 1.0 m | 1.05   0.41 | 2989.7      |
| 2.0 m | 2.10   0.82 | 747.4       |
| 3.0 m | 3.15   1.22 | 332.2       |
| 4.0 m | 4.20   1.63 | 186.9       |
| 5.0 m | 5.25   2.04 | 119.6       |
|       | Ø (m)       | E0(0°) [lx] |

