

## Intara RC 625

Article number: 50280005

### LIGHT TECHNOLOGY


|                      |          |
|----------------------|----------|
| LED                  | SMD Line |
| Light colour         | 830      |
| Luminous flux        | 3190 lm  |
| System power         | 33 W     |
| Luminaire Efficiency | 97 lm/W  |
| Reflector            | WallWash |
| Beam angle           | 1 x 20°  |

### LUMINAIRE

|                           |                      |
|---------------------------|----------------------|
| Weight                    | 0.9kg without driver |
| Protection rating . class | IP 20 . III          |
| Luminaire colour          | black                |

### OPTIONAL

Mounting Accessories  
DALI driver on request



recessed luminaire with LED, rated life of the LED L80/B10 > 50000 h, color rendering index CRI > 80, chromaticity point tolerance 3 SDCM (initial), Reflector with asymmetrical light distribution pattern, 99.99% pure aluminium reflector made of MIRO-SILVER®, aluminium luminaire housing and frame, anodized, separate driver unit.

If ceilings with thickness of more than 20mm are fitted the ceiling cutout will differ. Please pay attention to the dimension in the drawing.

76500032 driver unit, fix current  
220-240 V / 50-60 Hz, 900 mA, with GST18/3-pin connector, incl. 3-conductor feed-through wiring, camera-compatible, up to 2.5 KV interference resistance, SELV, max. 52 Stk. / B16 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.

