

# Intara RD 164

Article number: 50680019

## LIGHT TECHNOLOGY



|                      |          |
|----------------------|----------|
| LED                  | COB      |
| Light colour         | 830      |
| Luminous flux        | 4150 lm  |
| System power         | 34W      |
| Luminaire Efficiency | 122 lm/W |
| Reflector            | Flood    |
| Beam angle           | 30°      |

## LUMINAIRE

|                           |                      |
|---------------------------|----------------------|
| Rotation angle            | +175° / -175°        |
| Swivel angle              | +30° / -30°          |
| Weight                    | 0.8kg without driver |
| Protection rating . class | IP 20 . III          |
| Luminaire colour          | black                |

## OPCJA

RAL colours




Recessed luminaire with LED, rated life of the LED L80/B10 > 50000h, colour rendering index CRI > 80, chromaticity tolerance 2 SDCM (initial), axially symmetrical reflector with circular light distribution pattern, 99,99% pure aluminium, segmented and faceted, infinitely adjustable sheet steel luminaire housing, incl. glass cover, sheet metal powder coated, separate driver unit

76500076 driver unit, fix current  
220-240 V / 50-60 Hz, 850 mA, with GST18/3-pin connector, incl. 3-conductor feed-through wiring, camera-compatible, up to 2.5 KV interference resistance, SELV, max. 34 luminaires per circuit (B16A fuse)

76500077 driver unit, DALI  
220-240 V / 50-60 Hz, 850 mA, with GST18/5-pin connector, incl. 5-conductor feed-through wiring, up to 2.5 KV interference resistance, SELV, max. 24 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



|       |      |             |
|-------|------|-------------|
| 1.0 m | 0.48 | 10919.0     |
| 2.0 m | 0.96 | 2729.8      |
| 3.0 m | 1.44 | 1213.2      |
| 4.0 m | 1.92 | 682.4       |
| 5.0 m | 2.40 | 436.8       |
| Ø (m) |      | E0(0°) [lx] |

