

Intara RD 165

Article number: 51020105

LIGHT TECHNOLOGY


LED COB
Light colour GoldenBread
Luminous flux 2870 lm
System power 28 W
Luminaire Efficiency 103 lm/W
Reflector Spot
Beam angle 20°

LUMINAIRE

 $\begin{array}{lll} \text{Swivel angle} & 2 \times 25^{\circ} \\ \text{Weight} & 0.9 \text{ kg} \\ \text{Protection rating . class} & \text{IP 20 . III} \\ \text{Luminaire colour} & \text{stratoblack} \\ \end{array}$

OPTIONEEL

RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver





Recessed luminaire with LED, rated life of the LED L80/B10 > 50000 h, chromaticity tolerance 3 SDCM (initial), reflector with circular light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, luminaire head die-cast aluminium, powder-coated, swivel angle +25°/-25°, luminaire housing sheet steel, powder-coated, stratoblack, separate driver unit

76500035 driver unit, Fix Current, 220-240 V / 50-60 Hz, 700 mA, camera-compatible, up to 2.5 KV interference resistance, SELV, max. 34 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.

