

Intara RD 190

Article number: 51030171

LIGHT TECHNOLOGY


| | |
|----------------------|---------|
| LED | COB |
| Light colour | Sun |
| Luminous flux | 1740 lm |
| System power | 28 W |
| Luminaire Efficiency | 62 lm/W |
| Reflector | Flood |
| Beam angle | 40° |

LUMINAIRE

| | |
|---------------------------|-------------|
| Rotation angle | 170° |
| Swivel angle | 2 x 30° |
| Weight | 1.0 kg |
| Protection rating . class | IP 20 . III |
| Luminaire colour | stratoblack |

OPTIONAL


RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver



Recessed luminaire with LED, rated life of the LED L80/B10 > 50000 h, chromaticity tolerance 3 SDCM (initial), reflector with circular light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, rotation angle 170°, swivel angle +30°/-30°, luminaire housing sheet steel, powder-coated, stratoblack, separate driver unit

76500035 driver unit, Fix Current, 220-240 V / 50-60 Hz, 700 mA, camera-compatible, up to 2.5 KV interference resistance, SELV, max. 34 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



| | | |
|-------|------|------------|
| 1.0 m | 0.77 | 3367.0 |
| 2.0 m | 1.54 | 842.0 |
| 3.0 m | 2.31 | 375.0 |
| 4.0 m | 3.08 | 211.0 |
| 5.0 m | 3.85 | 135.0 |
| Ø (m) | | E0(0°)(lx) |

