

# Intara RD 190

Article number: 51040010

## LIGHT TECHNOLOGY


|                      |           |
|----------------------|-----------|
| LED                  | COB       |
| Light colour         | 830       |
| Luminous flux        | 4230 lm   |
| System power         | 34 W      |
| Luminaire Efficiency | 126 lm/W  |
| Reflector            | OvalBasic |
| Beam angle           | 60° x 30° |

## LUMINAIRE

|                           |             |
|---------------------------|-------------|
| Rotation angle            | 170°        |
| Swivel angle              | 2 x 30°     |
| Weight                    | 1.0 kg      |
| Protection rating . class | IP 20 . III |
| Luminaire colour          | stratowhite |

## OPCJA

RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver




Recessed luminaire with LED, rated life of the LED L80/B10 > 50000 h, colour rendering index CRI > 80, chromaticity tolerance 2 SDCM (initial), reflector with oval light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, rotation angle 170°, swivel angle +30°/-30°, luminaire housing sheet steel, powder-coated, stratowhite, separate driver unit

76500076 driver unit, Fix Current, 220-240 V / 50-60 Hz, 850 mA, camera-compatible, up to 2.5 KV interference resistance, SELV, max. 34 luminaires per circuit (B16A fuse)

76500077 driver unit, DALI, 220-240 V / 50-60 Hz, 850 mA, with GST18/5-pin connector, incl. 5-conductor feed-through wiring, camera-compatible, up to 2.5 KV interference resistance, SELV, max. 24 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



|       |             |        |
|-------|-------------|--------|
| 1.0 m | 1.05 0.41   | 6586.8 |
| 2.0 m | 2.10 0.82   | 1646.7 |
| 3.0 m | 3.15 1.22   | 731.9  |
| 4.0 m | 4.20 1.63   | 411.7  |
| 5.0 m | 5.25 2.04   | 263.5  |
| Ø (m) | E0(0°) [lx] |        |

