

# Intara RD 190

Article number: 51050171

## LIGHT TECHNOLOGY

|                      |         |
|----------------------|---------|
| LED                  | COB     |
| Light colour         | Sun     |
| Luminous flux        | 1740 lm |
| System power         | 28 W    |
| Luminaire Efficiency | 62 lm/W |
| Reflector            | Spot    |
| Beam angle           | 20°     |

## LUMINAIRE

|                           |             |
|---------------------------|-------------|
| Rotation angle            | 170°        |
| Swivel angle              | 2 x 30°     |
| Weight                    | 1.0 kg      |
| Protection rating . class | IP 20 . III |
| Luminaire colour          | stratoblack |

## OPCJA

RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver



Recessed luminaire with LED, rated life of the LED L80/B10 > 50000 h, chromaticity tolerance 3 SDCM (initial), reflector with circular light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, rotation angle 170°, swivel angle +30°/-30°, luminaire housing sheet steel, powder-coated, stratoblack, separate driver unit

76500035 driver unit, Fix Current, 220-240 V / 50-60 Hz, 700 mA, camera-compatible, up to 2.5 KV interference resistance, SELV, max. 34 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.

