

Intara RD 190

Article number: 51140107

LIGHT TECHNOLOGY


LED	COB
Light colour	SpecialMeat
Luminous flux	2490 lm
System power	47 W
Luminaire Efficiency	52 lm/W
Reflector	Spot
Beam angle	20°

LUMINAIRE

Rotation angle	170°
Swivel angle	2 x 30°
Weight	1.3 kg
Protection rating . class	IP 20 . III
Luminaire colour	stratosilver

OPCJA

RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver




Recessed luminaire with LED, rated life of the LED L80/B10 > 50000 h, chromaticity tolerance 2 SDCM (initial), reflector with circular light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, rotation angle 170°, swivel angle +30°/-30°, luminaire housing sheet steel, powder-coated, stratosilver, separate driver unit

76500092 driver unit, Fix Current,
220-240 V / 50-60 Hz, 1200 mA, camera-compatible, up to 2.5 KV interference resistance, SELV, max. 24 luminaires per circuit (B16A fuse)

76500093 driver unit, DALI,
220-240 V / 50-60 Hz, 1200 mA, with GST18/5-pin connector, incl. 5-conductor feed-through wiring, camera-compatible, up to 2.5 KV interference resistance, SELV, max. 30 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



1.0 m	0.31	15038.1
2.0 m	0.62	3759.5
3.0 m	0.93	1670.9
4.0 m	1.24	939.9
5.0 m	1.55	601.5
Ø (m)		E0(0°) [lx]

