

## Intara SQ 174

Article number: 50670032

### LIGHT TECHNOLOGY


|                      |          |
|----------------------|----------|
| LED                  | COB      |
| Light colour         | 835      |
| Luminous flux        | 4340 lm  |
| System power         | 41 W     |
| Luminaire Efficiency | 106 lm/W |
| Reflector            | Flood    |
| Beam angle           | 30°      |

### LUMINAIRE

|                           |             |
|---------------------------|-------------|
| Swivel angle              | +30° / -30° |
| Weight                    | 2,0 kg      |
| Protection rating . class | IP 20 . III |
| Luminaire colour          | stratowhite |

### OPTIONEEL

RAL colours




Recessed luminaire with LED, rated life of the LED L80/B10 > 50000 h, colour rendering index CRI > 80, chromaticity tolerance 2 SDCM (initial), reflector with circular light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, cardanic, swivel angle +30°/-30°, luminaire housing sheet steel, powder-coated, stratowhite, separate driver unit

76500037 driver unit, fix current  
220-240 V / 50-60 Hz, 1050 mA, with GST18/3-pin connector, incl. 3-conductor feed-through wiring, camera-compatible, up to 2.5 KV interference resistance, SELV, max. 22 luminaires per circuit (B16A fuse)

76500042 driver unit, DALI  
220-240 V / 50-60 Hz, 1050 mA, with GST18/5-pin connector, incl. 5-conductor feed-through wiring, camera-compatible, up to 2.5 KV interference resistance, SELV, max. 52 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



|       |      |             |
|-------|------|-------------|
| 1.0 m | 0.48 | 12912.4     |
| 2.0 m | 0.96 | 3228.1      |
| 3.0 m | 1.44 | 1434.7      |
| 4.0 m | 1.92 | 807.0       |
| 5.0 m | 2.40 | 516.5       |
| Ø (m) |      | E0(0°) [lx] |

