

Intara XR

Article number: 50870019

LIGHT TECHNOLOGY


| | |
|----------------------|------------|
| LED | COB |
| Light colour | PearlWhite |
| Luminous flux | 1500 lm |
| System power | 15 W |
| Luminaire Efficiency | 110 lm/W |
| Reflector | Spot |
| Beam angle | 20° |

LUMINAIRE

| | |
|---------------------------|-------------|
| Swivel angle | +25°/ -25° |
| Weight | 0.69 kg |
| Protection rating . class | IP 20 . II |
| Luminaire colour | stratowhite |

OPTIONAL


RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver



Recessed luminaire with LED, rated life of the LED L80/B10 > 50000 h, colour rendering index CRI > 90, chromaticity tolerance 2 SDCM (initial), rotation-symmetrical reflector with circular light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, segmented and faceted, 3D lens silicon to reduce the proportion of scattered light, die-cast aluminium, powder-coated, rotation angle , swivel angle +25°/ -25°, stratowhite,

Inclusiv fix conected driver unit
220-240 V~ / 50-60 Hz, max. 36 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



| | | |
|-------|------|-------------|
| 1.0 m | 0.34 | 9126.9 |
| 2.0 m | 0.68 | 2281.7 |
| 3.0 m | 1.02 | 1014.1 |
| 4.0 m | 1.36 | 570.4 |
| 5.0 m | 1.70 | 365.1 |
| Ø (m) | | E0(0°) [lx] |

