

## Intara XR

Article number: 50890063

### LIGHT TECHNOLOGY


|                      |         |
|----------------------|---------|
| LED                  | COB     |
| Light colour         | BeCool  |
| Luminous flux        | 2830 lm |
| System power         | 34 W    |
| Luminaire Efficiency | 83 lm/W |
| Reflector            | Flood   |
| Beam angle           | 40°     |

### LUMINAIRE

|                           |             |
|---------------------------|-------------|
| Swivel angle              | +25° / -25° |
| Weight                    | 0.69 kg     |
| Protection rating . class | IP 20 . II  |
| Luminaire colour          | stratowhite |

### OPTIONAL


RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver



Recessed luminaire with LED, rated life of the LED L80/B10 > 50000 h, colour rendering index CRI > 96, chromaticity tolerance 2 SDCM (initial), reflector with circular light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, segmented and faceted, die-cast aluminium, powder-coated, rotation angle , swivel angle +25° / -25°, stratowhite,

Inclusiv fix connected driver unit  
220-240 V~ / 50-60 Hz, max. 18 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



|       |       |             |
|-------|-------|-------------|
| 1.0 m | 0.81  | 4979.7      |
| 2.0 m | 1.62  | 1244.9      |
| 3.0 m | 2.43  | 553.3       |
| 4.0 m | 3.24  | 311.2       |
| 5.0 m | 4.05  | 199.2       |
|       | Ø (m) | E0(0°) [lx] |

