

Intara XR

Article number: 50760020

LIGHT TECHNOLOGY


| | |
|----------------------|---------|
| LED | COB |
| Light colour | BeCool |
| Luminous flux | 3060 lm |
| System power | 41 W |
| Luminaire Efficiency | 75 lm/W |
| Reflector | Medium |
| Beam angle | 25° |

LUMINAIRE

| | |
|---------------------------|-------------|
| Rotation angle | 400° |
| Swivel angle | +85°/-85° |
| Weight | 0.65 kg |
| Protection rating . class | IP 20 . II |
| Luminaire colour | stratowhite |

OPTIONAL


RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver



Semi-recessed luminaire with LED, rated life of the LED L80/B10 > 50000 h, colour rendering index CRI > 96, chromaticity tolerance 2 SDCM (initial), reflector with circular light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, segmented and faceted, 3D lens silicon to reduce the proportion of scattered light, die-cast aluminium, powder-coated, rotation angle 400°, swivel angle +85°/-85°, stratowhite, potentiometer to adjust the brightness, separate driver unit

76500109 driver unit, Fix Current, 220-240 V / 50-60 Hz, 1050 mA, camera-compatible, up to 2.5 KV interference resistance, SELV, max. 22 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



| | | |
|-------|------|-------------|
| 1.0 m | 0.44 | 12106.0 |
| 2.0 m | 0.88 | 3026.5 |
| 3.0 m | 1.32 | 1345.1 |
| 4.0 m | 1.76 | 756.6 |
| 5.0 m | 2.20 | 484.2 |
| Ø (m) | | E0(0°) [lx] |

