

Ontero IC

Article number: 21430020

LIGHT TECHNOLOGY


LED COB
Light colour BeCool
Luminous flux 1080 lm
System power 15 W
Luminaire Efficiency 72 lm/W
Reflector NarrowSpot
Beam angle 10°

LUMINAIRE

Rotation angle 330°
Swivel angle +90°/-90°
Weight 1.1 kg
Protection rating . class IP 20 . II
Luminaire colour stratowhite

OPTIONEEL

RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver, Casambi model on inquiry







Surface-mounted luminaire with LED, rated life of the LED L80/B10 > 50000 h, colour rendering index CRI > 96, chromaticity tolerance 2 SDCM (initial), LED hybrid technology, 3D silicone lens to reduce the proportion of scattered light, rotation-symmetrical reflector with circular light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, segmented and faceted, exchangeable reflector unit in high-sheen black plastic, with glass cover, rotation angle 330°, swivel angle +90°/-90°, luminaire head/retention arm diecast aluminium, stratowhite

In-Track-Adapter, Fix Current, white, max. 50 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.













www.baero.com 17.10.2025