

## Ontero IC

Article number: 21470086

### LIGHT TECHNOLOGY

|                      |             |
|----------------------|-------------|
| LED                  | COB         |
| Light colour         | GoldenBread |
| Luminous flux        | 3080 lm     |
| System power         | 34 W        |
| Luminaire Efficiency | 91 lm/W     |
| Reflector            | OvalBasic   |
| Beam angle           | 60° x 40°   |

### LUMINAIRE

|                           |              |
|---------------------------|--------------|
| Rotation angle            | 330°         |
| Swivel angle              | +/- 90°      |
| Weight                    | 1.1 kg       |
| Protection rating . class | IP 20 . II   |
| Luminaire colour          | stratosilver |

### OPTIONAL

RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, changeable reflector, honeycomb louver, Casambi model on inquiry



Surface-mounted luminaire with LED, rated life of the LED L80/B10 > 50000 h, chromaticity tolerance 3 SDCM (initial), LED hybrid technology, 3D silicone lens to reduce the proportion of scattered light, reflector with oval light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, segmented, exchangeable reflector unit in high-sheen black plastic, with glass cover, luminaire head die-cast aluminium, powder-coated, rotation angle 330°, swivel angle +/-90°, luminaire head/retention arm die-cast aluminium, stratosilver

In-Track-Adapter, Fix Current, black,  
max. 50 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



| Height (m) | Beam Diameter (m) | Beam Diameter (ft) | Footcandle (lx) |
|------------|-------------------|--------------------|-----------------|
| 1.0 m      | 1.18              | 0.76               | 3476.5          |
| 2.0 m      | 2.36              | 1.52               | 869.1           |
| 3.0 m      | 3.54              | 2.28               | 386.3           |
| 4.0 m      | 4.72              | 3.04               | 217.3           |
| 5.0 m      | 5.90              | 3.80               | 139.1           |

Ø (m) E0(0°) [lx]

