

Ontero IC

Article number: 21470103

LIGHT TECHNOLOGY


LED COB
Light colour 927
Luminous flux 3530 lm
System power 41 W
Luminaire Efficiency 86 lm/W
Reflector OvalBasic
Beam angle 60° x 40°

LUMINAIRE

Rotation angle 330°
Swivel angle +90°/-90°
Weight 1.1 kg
Protection rating . class IP 20 . II
Luminaire colour stratoblack

OPCJA

RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, changeable reflector, honeycomb louver, Casambi model on inquiry






Surface-mounted luminaire with LED, rated life of the LED L80/B10 > 50000 h, colour rendering index CRI > 90, chromaticity tolerance 2 SDCM (initial), LED hybrid technology, 3D silicone lens to reduce the proportion of scattered light, reflector with oval light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, segmented, exchangeable reflector unit in high-sheen black plastic, with glass cover, luminaire head die-cast aluminium, powder-coated, rotation angle 330°, swivel angle +90°/-90°, luminaire head/retention arm die-cast aluminium, stratoblack

Multiadapter black, inclusive driver unit: 220-240 V~ / 50-60 Hz, max. 64 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.











www.baero.com 17.10.2025