

## Ontero IC

Article number: 21480043

## LIGHT TECHNOLOGY


LED COB
Light colour SpecialMeat
Luminous flux 1340 lm
System power 23 W
Luminaire Efficiency 58 lm/W
Reflector WallBeam

## **LUMINAIRE**

Rotation angle 330°
Swivel angle +/- 90°
Weight 1.1 kg
Protection rating . class IP 20 . II
Luminaire colour stratoblack

## **OPCJA**

RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, changeable reflector, Casambi model on inquiry






Surface-mounted luminaire with LED, rated life of the LED L80/B10 > 50000 h, chromaticity tolerance 2 SDCM (initial), reflector with asymmetrical light distribution pattern, primary reflector and kick reflector 99% pure aluminium in MIRO-Silver®, attachment with kick reflector to the ceiling approach of the light cone, exchangeable reflector unit in high-sheen black plastic, with glass cover, luminaire head die-cast aluminium, powder-coated, rotation angle 330°, swivel angle +/-90°, luminaire head/retention arm die-cast aluminium, stratoblack

In-Track-Adapter, Fix Current, black, max. 50 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.











www.baero.com 21.10.2025