

# Ontero IC

Article number: 21489069

## LIGHT TECHNOLOGY


|                      |          |
|----------------------|----------|
| LED                  | COB      |
| Light colour         | 840      |
| Luminous flux        | 4800 lm  |
| System power         | 41 W     |
| Luminaire Efficiency | 117 lm/W |
| Reflector            | WallBeam |

## LUMINAIRE

|                           |                |
|---------------------------|----------------|
| Rotation angle            | 330°           |
| Swivel angle              | +90° / -90°    |
| Weight                    | 1.1 kg         |
| Protection rating . class | IP 20 . II     |
| Luminaire colour          | special colour |

## OPCJA

RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, changeable reflector, Casambi model on inquiry



Surface-mounted luminaire with LED, rated life of the LED L80/B10 > 50000 h, colour rendering index CRI > 80, chromaticity tolerance 2 SDCM (initial), reflector with asymmetrical light distribution pattern, primary reflector and kick reflector 99% pure aluminium in MIRO-Silver®, attachment with kick reflector to the ceiling approach of the light cone, exchangeable reflector unit in high-sheen black plastic, with glass cover, luminaire head die-cast aluminium, powder-coated, rotation angle 330°, swivel angle +90°/-90°, luminaire head/retention arm die-cast aluminium, special colour

Multiadapter black, inclusive driver unit: 220-240 V~ / 50-60 Hz, max. 64 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.

