

## Ontero ID

Article number: 20610006

## LIGHT TECHNOLOGY


LED COB
Light colour BeCool
Luminous flux 1030 lm
System power 15 W
Luminaire Efficiency 69 lm/W
Reflector NarrowSpot
Beam angle 10°

## **LUMINAIRE**

Rotation angle 330°
Swivel angle 90°
Weight 1.3 kg
Protection rating . class IP 20 . I
Luminaire colour stratoblack

## OPCJA

RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver







Surface-mounted luminaire with LED, rated life of the LED L80/B10 > 50000 h, colour rendering index CRI > 96, chromaticity tolerance 2 SDCM (initial), LED hybrid technology, 3D silicone lens to reduce the proportion of scattered light, rotation-symmetrical reflector with circular light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, segmented and faceted, exchangeable reflector unit in high-sheen black plastic, with glass cover, rotation angle 330°, swivel angle 90°, luminaire housing die-cast aluminium, powder-coated, stratoblack

Multiadapter black, inclusive driver unit: 220-240 V~ / 50-60 Hz, max. 34 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.













www.baero.com 15.10.2025