

# Ontero ID

Article number: 20620017

## LIGHT TECHNOLOGY

|                      |          |
|----------------------|----------|
| LED                  | COB      |
| Light colour         | BeColor  |
| Luminous flux        | 1510 lm  |
| System power         | 15 W     |
| Luminaire Efficiency | 101 lm/W |
| Reflector            | Spot     |
| Beam angle           | 20°      |

## LUMINAIRE

|                           |              |
|---------------------------|--------------|
| Rotation angle            | 330°         |
| Swivel angle              | 90°          |
| Weight                    | 1.3 kg       |
| Protection rating . class | IP 20 . I    |
| Luminaire colour          | stratosilver |

## OPTIONAL


RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver



Surface-mounted luminaire with LED, rated life of the LED L80/B10 > 50000 h, colour rendering index CRI > 96, chromaticity tolerance 2 SDCM (initial), LED hybrid technology, 3D silicone lens to reduce the proportion of scattered light, reflector with circular light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, segmented and faceted, exchangeable reflector unit in high-sheen black plastic, with glass cover, rotation angle 330°, swivel angle 90°, luminaire housing die-cast aluminium, powder-coated, stratosilver

Multiadapter black, inclusive driver unit: 220-240 V~ / 50-60 Hz, max. 34 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



|       |      |            |
|-------|------|------------|
| 1.0 m | 0.34 | 9188.0     |
| 2.0 m | 0.68 | 2297.0     |
| 3.0 m | 1.02 | 1021.0     |
| 4.0 m | 1.36 | 575.0      |
| 5.0 m | 1.70 | 368.0      |
| Ø (m) |      | E0(0°)(lx) |

