

Ontero ID

Article number: 20650070

LIGHT TECHNOLOGY


LED COB
Light colour GoldenBread
Luminous flux 2330 lm
System power 23 W
Luminaire Efficiency 101 lm/W
Reflector OvalBasic
Beam angle 60° x 40°

LUMINAIRE

Rotation angle 330°
Swivel angle 90°
Weight 1.3 kg
Protection rating . class IP 20 . I
Luminaire colour stratowhite

OPTIONEEL

RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver







Surface-mounted luminaire with LED, rated life of the LED L80/B10 > 50000 h, chromaticity tolerance 3 SDCM (initial), LED hybrid technology, 3D silicone lens to reduce the proportion of scattered light, reflector with oval light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, segmented, exchangeable reflector unit in high-sheen black plastic, with glass cover, rotation angle 330°, swivel angle 90°, luminaire housing die-cast aluminium, powder-coated, stratowhite

Multiadapter black, inclusive driver unit: 220-240 V~ / 50-60 Hz, max. 34 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.















www.baero.com 16.10.2025