

## Ontero XR

Article number: 20550013

## LIGHT TECHNOLOGY


LED COB
Light colour BeCool
Luminous flux 1280 lm
System power 15 W
Luminaire Efficiency 85 lm/W
Reflector Flood
Beam angle 40°

## **LUMINAIRE**

Rotation angle 330°
Swivel angle +85° / -85°
Weight 0.54 kg
Protection rating . class IP 20 . II
Luminaire colour stratosilver

## OPCJA

RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry (only luminaire head and holding arm), surface alloys on inquiry, Casambi on inquiry, blends







Surface-mounted luminaire with LED, rated life of the LED L80/B10 > 50000 h, colour rendering index CRI > 96, chromaticity tolerance 3 SDCM (initial), reflector with circular light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, rotation angle 330°, swivel angle +85°/-85°, luminaire head/retention arm die-cast aluminium, powder-coated, stratosilver

In-Track-Adapter, black, inclusive driver unit, Fix Current, 220-240 V $_{\sim}$  / 50-60 Hz, max. 30 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.













www.baero.com 17.10.2025