

## Pendiro CP 300

Article number: 81100007

### LIGHT TECHNOLOGY

|                      |           |
|----------------------|-----------|
| LED                  | COB       |
| Light colour         | 835       |
| Luminous flux        | 4420 lm   |
| System power         | 34 W      |
| Luminaire Efficiency | 130 lm/W  |
| Reflector            | OvalBasic |
| Beam angle           | 60° x 40° |

### LUMINAIRE

|                           |              |
|---------------------------|--------------|
| Swivel angle              | +25° / -25°  |
| Weight                    | 3.2 kg       |
| Protection rating . class | IP 20 . I    |
| Luminaire colour          | stratosilver |

### OPTIONAL


RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver



Suspended luminaire with LED, rated life of the LED L80/B10 > 50000 h, colour rendering index CRI > 80, chromaticity tolerance 2 SDCM (initial), reflector with oval light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, luminaire shade die-cast aluminium, powder-coated, swivel angle +25°/-25°, luminaire housing sheet steel, powder-coated, stratosilver

Multiadapter black, inclusive driver unit: 220-240 V~ / 50-60 Hz, max. 24 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



|       |           |             |
|-------|-----------|-------------|
| 1.0 m | 1.05 0.41 | 6633.5      |
| 2.0 m | 2.10 0.82 | 1658.4      |
| 3.0 m | 3.15 1.22 | 737.1       |
| 4.0 m | 4.20 1.63 | 414.6       |
| 5.0 m | 5.25 2.04 | 265.3       |
| Ø (m) |           | E0(0°) [lx] |

